



DRIVESHAFT AND BEARINGS MANUFACTURE C...

200 mm x 420 mm x 138 mm NSK NU2340EM cylindrical roller bearings

Bearing No. NU2340EM



NU2340EM Bearing 2D drawings and 3D CAD models

Size	200x420x138 mm
Bore Diameter	200 mm
Outer Diameter	420 mm
Width	138 mm
d	200 mm
Fw	253 mm
D	420 mm
B	138 mm
C	138 mm
r min.	5 mm
r1 min.	5 mm
da min.	220 mm
Da max.	400 mm
db max.	247 mm
db min	220 mm
ra max.	4 mm
rb max.	4 mm
S	7,7 mm
Weight	99,3 Kg
Basic dynamic load rating (C)	1910 kN
Basic static load rating (C0)	2760 kN
(Grease) Lubrication Speed	1 200 r/min
hidYobi	NU2340EM
LangID	1
D_	420



DRIVESHAFT AND BEARINGS MANUFACTURE C...

Macha rpm	1900
B_	138
hidTable	ecat_NSCLDR
Oil rpm	1500
rb	4
mass	98
GRS rpm	1200
ra	4
db max	247
TSR rpm	1300
C0	2760
DE_	369
Prod_Type3	CRB_SR_NU
da	220
DA_	58
Z_	14
D_a max	400
yobi	NU2340EM
dd min	283
C_conv	1910000
ALPHA_	0
SDM_	311
r	5
dc min	263
KBRG	4145
SBRG	23
r1	5
DI_	253