



**200 mm x 420 mm x 138 mm NSK  
NUP2340EM cylindrical roller bearings**

Bearing No. NUP2340EM

NUP2340EM Bearing 2D drawings and 3D CAD models

Size	200x420x138 mm
Bore Diameter	200 mm
Outer Diameter	420 mm
Width	138 mm
d	200 mm
Fw	253 mm
D	420 mm
B	138 mm
C	138 mm
r min.	5 mm
r1 min.	5 mm
da min.	220 mm
Da max.	400 mm
db max.	247 mm
db min	220 mm
ra max.	4 mm
rb max.	4 mm
S	7,7 mm
Db max	400 mm
Weight	99,3 Kg
Basic dynamic load rating (C)	1910 kN
Basic static load rating (C0)	2760 kN
(Grease) Lubrication Speed	1200 r/min
hidYobi	NUP2340EM
LangID	1



## DRIVESHAFT AND BEARINGS MANUFACTURE C...

D_	420
Macha rpm	1900
B_	138
hidTable	ecat_NSCLDR
Oil rpm	1500
rb	4
mass	102
GRS rpm	1200
ra	4
db max	247
TSR rpm	1300
C0	2760
DE_	369
Prod_Type3	CRB_SR_NUP
da	220
DA_	58
Z_	14
D_a max	400
yobi	NUP2340EM
dd min	283
C_conv	1910000
ALPHA_	0
SDM_	311
r	5
dc min	263
KBRG	4165
SBRG	23
r1	5
DI_	253